

Indian Institute of Technology Kanpur
Department of Electrical Engineering

Ref No. EE/SERB/PKP/2015/APR

Date: 10th June 2015

Sealed quotations are invited for the following equipment's/ Components

The quotations should reach us by 26th June 2015. Please send the quotations to

Dr. Pradeep Kumar K

Assistant Professor

Department of Electrical Engineering

IIT Kanpur

Kanpur-208016, India

You can email the soft copy of quotations to serbqkd@gmail.com on or before 26th June 2015.

Sl. No	Item description (including test equipment, components, materials etc.)	Qty
1	Single-photon counting module (C-band, TEC cooled, NEP = $1\text{pW/Hz}^{1/2}$ or better) with accessories (power chords, software, etc)	2
2	Avalanche photodiodes Part No. CMC 264-339769-101	2
3	Avalanche photodiodes Part No. NR8360JP-BC	2
4	EDFA gain module (C-band, +35 dB or better gain small signal gain, Max power output: 10 mW or better) along with accessories	2
5	Laser diode driver with TEC controller, maximum supply current 500 mA, bench top module, accessories--power chords, cables, connectors, software etc must be included.	1
6	Laser driver (up to 500 mA) and TEC controller along with Laser diode mounts (butterfly packaged LD)	2
7	Standard single-mode fiber G.652 <ul style="list-style-type: none"> • 5 km spool with FC/PC connectors • 25 km spool with FC/PC connectors • 100 km spool with FC/PC connectors 	One each
8	Scanning FP spectrum analyzer module (C-band, FSR 10 GHz) + control box for spectrum analyzer	1
9	PZT based single-mode fiber stretcher module, 600-1625 nm wavelength range, 2 rad/wavelength/volt or lower, Total delay ~ 0.5 ps, FC/PC connectorized	1
10	RF gain block with Max output power 1 W <ul style="list-style-type: none"> • 2.5 GHz central frequency • 5.2 GHz central frequency Or a broadband (2-5 GHz frequency range) single gain block	Two each
14	LM3940 3.3V Voltage regulator (TO263 Package)	2
15	LT3482 70V Voltage regulator (16 lead plastic QFN package)	2
16	ADN2880 Transimpedance Amplifier	2
17	ADA4817-2 OPAMP (16 lead LFCSP package)	2
18	RF Connectors/adapters and adapters <ul style="list-style-type: none"> • 1.85 mm GPO female and male 	• 4 each

19	RF cables GPO (SMP) female jack to SMA male jack, length=50 cm	4
20	Altera Arria V GT FPGA Development Kit, power supply, all relevant cables (USB, PCI Express etc.), Altera IP Software Ethernet daughter board interfaceable with Altera Arria V GT FPGA FPGA board	2
21	Analog to Digital Converters (4 GSPS or better) with board interfaceable to Altera Arria V GT FPGA FPGA	2
22	Digital to Analog Converters (4 GSPS or better, 8-bit) with board interfaceable D Altera Arria V GT FPGA	2
23	Highly nonlinear fiber: PM maintaining, FC/PC connectorized, length 100m, low dispersion slope (0.025ps/nm ² -km) or zero dispersion slope, operating wavelength 1550nm	1

Note: All fiber-optic components/modules must be connectorized with FC/PC or FC/APC connectors.

1. Maximum education discount, if any should be offered.
2. Validity of quotation should be at least for 60 days.
3. Prices should be on CIF and FOB separately (if imported).
4. Normal payment terms for the Institute will be applicable (90% on delivery of the items and the remaining 10% after satisfactory installation/ inspection)
5. Quotation should carry proper certifications like agency certificate, proprietary certificate, etc.