

# Lecture 7: Experiment 6

## EE380 (Control Systems)

Manavaalan  
Gunasekaran

PhD student

manvaal@iitk.ac.in

Arun Kant  
Singh

PhD student

arunkant@iitk.ac.in

Ramprasad  
Potluri

Associate Professor

potluri@iitk.ac.in

Department of Electrical Engineering  
Indian Institute of Technology Kanpur

September 23, 2011



Back

Forward

Close


# Contents

<b>1</b>	<b>Outline of the experiment</b>	<b>3</b>
<b>2</b>	<b>Background</b>	<b>4</b>
<b>3</b>	<b>Simulink demo</b>	<b>7</b>
<b>4</b>	<b>Practical results: PS at 12 V</b>	<b>8</b>
<b>5</b>	<b>Practical results: PS at 20 V &amp; using string</b>	<b>10</b>
<b>6</b>	<b>Practical results: PS at 20 V &amp; using wire</b>	<b>13</b>
<b>7</b>	<b>Homework (HW) vs. Lab work (LW)</b>	<b>21</b>

[Back](#)[Forward](#)[Close](#)

# Outline of the experiment

- Build two DOF controller with disturbance observer (DOB).




- First DOF provided by DOB in middle loop.
- Second DOF provided by speed controller  $K_\omega(s)$  in outer loop.
- Shaded portion of block diagram is implemented in dsPIC.


# Background

## Two degree of freedom control

- Single DOF controller:



- Two DOF controller



- $C_a(s)$  provides one degree of freedom while  $C_b(s)$  provides the other.
- $C_b(s)$  helps reject  $T_L$ , while  $C_a(s)$  helps track  $\omega_d$ .




Back

Forward

Close


## Implementation of $C_b(s)$ : DOB

- Current control designed in previous experiment.



Plant: The part outside dsPIC30F4012


- Used  $\hat{i} \approx i_{\text{sens}}/1.8 - 1/30$ . Seems a good approximation.
- Representation of motor unit with  $i$  well regulated at  $i_d$ .




## DOB (continued)

6/21

- Open-loop DOB to estimate  $T_L$ :



- Purpose of  $1/(\tau s + 1)$ : □ to make inversion of  $\frac{1}{Js + B}$  practically possible, □ to improve disturbance rejection.
- Closed-loop DOB to estimate  $T_L$ :



Back


Forward

Close


# Simulink demo

- Larger the  $\tau$ , poorer the disturbance rejection.
- Trade-off with  $\tau$ : dist. rej. versus noise rej.
- Effect of noise.
- Effect of breaking feedback of  $\hat{i}_L$ .
- Effect of moving node \* to after filter.

Part implemented in exp-t on "Control of armature current"



# Practical results: PS at 12 V




Back

Forward

Close



- But  $u$  is saturating.



- So, work with power supply providing 15 V to H-bridge.




Back


Forward

Close

# Practical results: PS at 20 V & using string



- Note that  $\hat{T}_L \approx 0.004$  Nm.



- Note that  $u$  is almost reaching 20 V, not saturating. Good!
- But,  $\omega$  deviates 20 rad/s from mean value after  $T_L$  appears. Bad!
- Also, details of disturbance rejection blurred.




Back

Forward

Close

- Without DOB.
- But, cannot say how poorly disturbance is rejected.
- Also,  $\hat{T}_L \approx 0.003 \text{ Nm}$ , while with DOB it was 0.004.




Back

Forward


Close

# Practical results: PS at 20 V & using wire



- Deviation in  $\omega$  after disturbance appears  $\approx 10$  rad/s. Improved!

- Results of `terminal.log`, filtered.



- $\hat{T}_L \approx 0.0025$  Nm. Explanation: string was making the radius of pulley larger than wire is making.




Back

Forward


Close

- More results with DOB.

15/21



- And, filtered results of `terminal.log`.




Back

Forward

Close






Back

Forward



Close



Back

Forward



Close



Back

Forward

Close



Back

Forward

Close

# Homework (HW) vs. Lab work (LW)

See the lab manual.



Back

Forward

Close